

IEC SYSTEM FOR CONFORMITY TESTING  
AND CERTIFICATION OF ELECTRICAL  
EQUIPMENT (IECEE)  
CB SCHEME

SYSTÈME CEI D'ESSAIS DE CONFORMITÉ  
ET DE CERTIFICATION DES ÉQUIPEMENTS  
ÉLECTRIQUES (IECEE)  
METHODE OC

CB TEST CERTIFICATE  
CERTIFICAT D'ESSAI OC

Product  
*Produit*

Name and address of the applicant  
*Nom et adresse du demandeur*

Name and address of the manufacturer  
*Nom et adresse du fabricant*

Name and address of the factory  
*Nom et adresse de l'usine*

Rating and principal characteristics  
*Valeurs nominales et caractéristiques principales*

Trade mark (if any)  
*Marque de fabrique (si elle existe)*

Model/type Ref.  
*Ref. de type*

Additional information (if necessary)  
*Information complémentaire (si nécessaire)*

A sample of the product was tested and found  
to be in conformity with  
*Un échantillon de ce produit a été essayé et a été  
considéré conforme à la*

as shown in the Test Report Ref. No.  
which form part of this certificate  
*comme indiqué dans le Rapport d'essais numéro  
de référence*  
*qui constitue une partie de ce certificat*

Switch Mode Power Supply (DIN Rail)

Puls Elektronische Stromversorgungen GmbH  
Arabellastr 15  
81925 Munich, Germany

Puls Elektronische Stromversorgungen GmbH  
Arabellastr 15  
81925 Munich, Germany

Puls EP K.S.  
Ul. Alfonse Muchy 5473  
430 01 Chomutov, Czech Republic

100-120/ 200-240Vac, 50-60Hz, 5/2.7A, Class I

CS10.KKX-XX,  
where KK represents the output voltage and can be 24V to  
52V, X can be any character or number, not safety relevant.  
where KK is 24: Output: 24-28Vdc, 10-8.6A, 240W  
where KK is 48: Output: 48-52Vdc, 5.0-4.6A, 240W

PUBLICATION

EDITION

IEC 60950-1:2001

1"

E137006-A13-CB-1

This CB Test Certificate is issued by the National Certification Body  
*Ce Certificate d'essai OC est établi par l'Organisme National de Certification*

Date 2006-03-30

Signature

Karina Christiansen  
Certification Manager



An Affiliate of  
**Underwriters  
Laboratories Inc.®**

**UL International Demko A/S**  
Lyskaer 8, P.O. Box 514  
DK-2730 Herlev, Denmark  
Telephone: +45 44856565  
Fax: +45 44856500

Internal Ref.:  
Manfred Mueller

## **COVER PAGE FOR TEST REPORT**

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Item Description:                                                                                                                                                                                                                                                                                                                                                                                                                                             | Switch Mode Power Supply (DIN Rail)                                                                                                                 |
| Model/Type Reference:                                                                                                                                                                                                                                                                                                                                                                                                                                              | CS10.KKX-XX, where KK represents the output voltage and can be 24V to 52V, X can be any character or number, not safety relevant.                   |
| Rating(s):                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Input: 100-120/ 200-240Vac, 50-60Hz, 5/2.7A;<br>where KK is 24: Output: 24-28Vdc, 10-8.6A, 240W<br>where KK is 48: Output: 48-52Vdc, 5.0-4.6A, 240W |
| Standards:                                                                                                                                                                                                                                                                                                                                                                                                                                                         | IEC 60950-1:2001, First Edition                                                                                                                     |
| Applicant Name and Address:                                                                                                                                                                                                                                                                                                                                                                                                                                        | PULS ELEKTRONISCHE STROMVERSORGUNGEN<br>GMBH<br>ARABELLASTR 15<br>81925 MUNICH GERMANY                                                              |
| Factory Location(s):                                                                                                                                                                                                                                                                                                                                                                                                                                               | PULS EP K.S.<br>UL. ALFONSE MUCHY 5473<br>430 01 CHOMUTOV, CZECH REPUBLIC                                                                           |
| <p>This Report includes the following parts, in addition to this cover page:</p> <ol style="list-style-type: none"><li>1. Specific Technical Criteria</li><li>2. Clause Verdicts</li><li>3. Critical Components</li><li>4. Test Results</li><li>5. Enclosures<ol style="list-style-type: none"><li>a. National Differences</li><li>b. Photographs</li><li>c. Diagrams</li><li>d. Schematics + PWB</li><li>e. Miscellaneous</li><li>f. Licenses</li></ol></li></ol> |                                                                                                                                                     |
| <p>All applicable tests according to the above standard(s) have been carried out.<br/>Test results are valid only for the tested equipment.<br/>This Test Report can be reproduced only in whole.<br/>Amendments and corrections can be reproduced only with the original CB Test Report.<br/>Written permission from UL International Demko A/S is required if the test report is copied in part.</p>                                                             |                                                                                                                                                     |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                   |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| <b>TEST REPORT</b><br><b>IEC 60950-1, First Edition</b><br><b>Information technology equipment - Safety -</b><br><b>Part 1: General Requirements</b>                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                   |
| <b>Report Reference No</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | E137006-A13-CB-1                                                                                                                  |
| <b>Tested by (+ signature)</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Thomas Weißbach                                                                                                                   |
| <b>Authorized by (+ signature)</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Michaela Zielke                                                                                                                   |
| <b>Supervised by (+ signature)</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Manfred Mueller                                |
| <b>Date of issue</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 2006-03-17                                                                                                                        |
| <b>CB Testing Laboratory</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | UL International Demko A/S                                                                                                        |
| <b>Address</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Lyskaer 8, 2730, Herlev, Denmark                                                                                                  |
| <b>Testing location/procedure</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | CBTL [ ] SMT [x] TMP [ ] WMT [ ]                                                                                                  |
| <b>Address</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | PULS ELEKTRONIK GMBH, Niederwaldstraße 3, D-09123 Chemnitz, Germany                                                               |
| <b>Applicant's name</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | PULS ELEKTRONISCHE STROMVERSORGUNGEN GMBH                                                                                         |
| <b>Address</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | ARABELLASTR 15<br>81925 MUNICH GERMANY                                                                                            |
| <b>Test specification:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                   |
| <b>Standard</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | IEC 60950-1:2001, First Edition                                                                                                   |
| <b>Test procedure</b> :                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | CB Scheme                                                                                                                         |
| <b>Non-standard test method</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | N/A                                                                                                                               |
| <b>Test Report Form No.</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | IEC60950__1A                                                                                                                      |
| <b>TRF originator</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | SGS Fimko Ltd                                                                                                                     |
| <b>Master TRF</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | dated 2002-03                                                                                                                     |
| <b>Copyright © 2003 IEC System for Conformity Testing and Certification of Electrical Equipment (IECEE), Geneva, Switzerland. All rights reserved.</b><br><br>This publication may be reproduced in whole or in part for non-commercial purposes as long as the IECEE is acknowledged as copyright owner and source of the material. IECEE takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. |                                                                                                                                   |
| <b>Test item description</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Switch Mode Power Supply (DIN Rail)                                                                                               |
| <b>Trade Mark</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | None                                                                                                                              |
| <b>Model/Type reference</b> :                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | CS10.KKX-XX, where KK represents the output voltage and can be 24V to 52V, X can be any character or number, not safety relevant. |
| <b>Manufacturer</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | PULS ELEKTRONIK, GMBH, Niederwaldstraße 3, D-09123 Chemnitz, Germany                                                              |
| <b>Rating</b> .....                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Input: 100-120/ 200-240Vac, 50-60Hz, 5/2.7A;<br>where KK is 24: Output: 24-28Vdc, 10-8.6A, 240W                                   |

where KK is 48: Output: 48-52Vdc, 5.0-4.6A, 240W

Marking Plate - Refer to Enclosure titled Miscellaneous for copy.

**Particulars: test item vs. test requirements**

|                                       |                      |
|---------------------------------------|----------------------|
| Equipment mobility :                  | for building-in      |
| Operating condition :                 | continuous           |
| Mains supply tolerance (%) :          | AC Mains: +10%, -10% |
| Tested for IT power systems :         | Yes                  |
| IT testing, phase-phase voltage (V) : | 240                  |
| Class of equipment :                  | Class I (earthed)    |
| Mass of equipment (kg) :              | < 1kg                |
| Protection against ingress of water : | N/A                  |

**Possible test case verdicts:**

|                                               |           |
|-----------------------------------------------|-----------|
| - test case does not apply to the test object | : N / A   |
| - test object does meet the requirement       | : P(Pass) |
| - test object does not meet the requirement   | : F(Fail) |

**General remarks:**

**This report is not valid as a CB Test Report unless signed by an approved CB Testing Laboratory and appended to a CB Test Certificate issued by a NCB in accordance with IECEE 02.**

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

"(see Enclosure #)" refers to additional information appended to the report.

"(see appended table)" refers to a table appended to the report.

Throughout this report a point is used as the decimal separator.

**General Product Information:****Report Summary**

All applicable tests according to the referenced standard(s) have been carried out.

**Product Description**

The product is a Switch Mode Power Supply for DIN-Rail mounting.

**Model Differences**

Construction of Model CS10.24X-XX is identical to Model CS10.48X-XX except different output rating.

**Additional Information**

-

**Technical Considerations**

The product was submitted and tested for use at the maximum ambient temperature (T<sub>ma</sub>) permitted by the manufacturer's specification of: 45°C at output power = 288W; 60°C at output power = 240W; 70°C with derating of 75% rated load.

The means of connection to the mains supply is: Permanently connected (field wired)

The product is intended for use on the following power systems: TT, TN, IT

The normal mounting orientation is: Input downwards, output upwards. Other mounting orientations have been measured at a lower output current of 80%. Refer to heating test table for details.

**Engineering Conditions of Acceptability**

When installed in an end-product, consideration must be given to the following:

The following Production-Line tests are conducted for this product: Earthing Continuity, Electric Strength

The end-product Electric Strength Test is to be based upon a maximum working voltage of: 245Vrms, 388Vpk;

The following secondary output circuits are SELV: All outputs.

The following secondary output circuits are at hazardous energy levels: All outputs

The power supply terminals and/or connectors are: Suitable for field wiring

The maximum investigated branch circuit rating is: 20 A

The investigated Pollution Degree is: 2

Proper bonding to the end-product main protective earthing termination is: Required

An investigation of the protective bonding terminals has: Not been conducted

The following magnetic devices (e.g. transformers or inductor) are provided with an OBJY2 insulation system with the indicated rating greater than Class A (105°C): T1 (Class F);

The following end-product enclosures are required: Fire, Electrical

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|         |                                                                  |                |      |
|---------|------------------------------------------------------------------|----------------|------|
| 1       | <b>GENERAL</b>                                                   |                | Pass |
| 1.5     | Components                                                       |                | Pass |
| 1.5.1   | General                                                          |                | Pass |
|         | Comply with IEC 60950 or relevant component standard             |                | Pass |
| 1.5.2   | Evaluation and testing of components                             |                | Pass |
| 1.5.3   | Thermal controls                                                 |                | N/A  |
| 1.5.4   | Transformers                                                     | T1             | Pass |
| 1.5.5   | Interconnecting cables                                           |                | N/A  |
| 1.5.6   | Capacitors in primary circuits ..... :                           | Refer to LOCC. | Pass |
| 1.5.7   | Double insulation or reinforced insulation bridged by components |                | Pass |
| 1.5.7.1 | General                                                          |                | N/A  |
| 1.5.7.2 | Bridging capacitors                                              |                | N/A  |
| 1.5.7.3 | Bridging resistors                                               |                | N/A  |
| 1.5.7.4 | Accessible parts                                                 |                | Pass |
| 1.5.8   | Components in equipment for IT power systems                     |                | Pass |

|       |                                      |  |      |
|-------|--------------------------------------|--|------|
| 1.6   | <b>Power interface</b>               |  | Pass |
| 1.6.1 | AC power distribution systems        |  | Pass |
| 1.6.2 | Input current                        |  | Pass |
| 1.6.3 | Voltage limit of hand-held equipment |  | N/A  |
| 1.6.4 | Neutral conductor                    |  | Pass |

| IEC 60950-1 |                                                              |                                                                                                                             |         |
|-------------|--------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|---------|
| Clause      | Requirement + Test                                           | Result - Remark                                                                                                             | Verdict |
| 1.7         | <b>Marking and instructions</b>                              |                                                                                                                             | Pass    |
| 1.7.1       | Power rating                                                 |                                                                                                                             | Pass    |
|             | Rated voltage(s) or voltage range(s) (V) .....               | 100-120V/200-240V.                                                                                                          | Pass    |
|             | Symbol for nature of supply, for d.c. only .....             | Not required for component.                                                                                                 | N/A     |
|             | Rated frequency or rated frequency range (Hz)....            | 50 - 60Hz.                                                                                                                  | Pass    |
|             | Rated current (mA or A) .....                                | 5/2.7A                                                                                                                      | Pass    |
|             | Manufacturer's name or trademark or identification mark..... | Refer to Cover Page.                                                                                                        | Pass    |
|             | Type/model or type reference .....                           | Refer to Cover Page.                                                                                                        | Pass    |
|             | Symbol for Class II equipment only.....                      |                                                                                                                             | N/A     |
|             | Other symbols .....                                          |                                                                                                                             | N/A     |
|             | Certification marks .....                                    | UL/c-UL Recognition Mark                                                                                                    | Pass    |
| 1.7.2       | Safety instructions                                          |                                                                                                                             | N/A     |
| 1.7.3       | Short duty cycles                                            |                                                                                                                             | N/A     |
| 1.7.4       | Supply voltage adjustment .....                              | Equipment is auto-ranging.                                                                                                  | N/A     |
| 1.7.5       | Power outlets on the equipment.....                          |                                                                                                                             | N/A     |
| 1.7.6       | Fuse identification.....                                     | Fuse(s) provided with voltage, current, and special fusing characteristic marking as applicable.                            | Pass    |
| 1.7.7       | Wiring terminals                                             |                                                                                                                             | Pass    |
| 1.7.7.1     | Protective earthing and bonding terminals.....               | The earth terminal is marked with the standard earth symbol (60417-2-IEC-5019) near the terminal. (refer to enclosure 7-02) | Pass    |
| 1.7.7.2     | Terminal for a.c. mains supply conductors                    |                                                                                                                             | Pass    |
| 1.7.7.3     | Terminals for d.c. mains supply conductors                   |                                                                                                                             | N/A     |
| 1.7.8       | Controls and indicators                                      |                                                                                                                             | N/A     |
| 1.7.8.1     | Identification, location and marking .....                   |                                                                                                                             | N/A     |
| 1.7.8.2     | Colours .....                                                |                                                                                                                             | N/A     |
| 1.7.8.3     | Symbols according to IEC 60417 .....                         |                                                                                                                             | N/A     |
| 1.7.8.4     | Markings using figures.....                                  |                                                                                                                             | N/A     |



| IEC 60950-1 |                                                 |                 |         |
|-------------|-------------------------------------------------|-----------------|---------|
| Clause      | Requirement + Test                              | Result - Remark | Verdict |
| 1.7.9       | Isolation of multiple power sources .....       |                 | N/A     |
| 1.7.10      | IT power distribution systems                   |                 | Pass    |
| 1.7.11      | Thermostats and other regulating devices        |                 | N/A     |
| 1.7.12      | Language.....                                   |                 | -       |
| 1.7.13      | Durability                                      |                 | N/A     |
| 1.7.14      | Removable parts                                 |                 | N/A     |
| 1.7.15      | Replaceable batteries                           |                 | N/A     |
|             | Language.....                                   |                 | -       |
| 1.7.16      | Operator access with a tool .....               |                 | N/A     |
| 1.7.17      | Equipment for restricted access locations ..... |                 | N/A     |

| IEC 60950-1 |                                                                     |                                                                                                    |         |
|-------------|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|---------|
| Clause      | Requirement + Test                                                  | Result - Remark                                                                                    | Verdict |
| 2           | <b>PROTECTION FROM HAZARDS</b>                                      |                                                                                                    | Pass    |
| 2.1         | Protection from electric shock and energy hazards                   |                                                                                                    | Pass    |
| 2.1.1       | Protection in operator access areas                                 | To be considered in end-use application.                                                           | Pass    |
| 2.1.1.1     | Access to energized parts                                           | To be considered in end-use application.                                                           | N/A     |
|             | Test by inspection.....:                                            |                                                                                                    | N/A     |
|             | Test with test finger.....:                                         |                                                                                                    | N/A     |
|             | Test with test pin.....:                                            |                                                                                                    | N/A     |
|             | Test with test probe.....:                                          |                                                                                                    | N/A     |
| 2.1.1.2     | Battery compartments.....:                                          |                                                                                                    | N/A     |
| 2.1.1.3     | Access to ELV wiring                                                |                                                                                                    | N/A     |
|             | Working voltage (V); minimum distance (mm) through insulation.....: |                                                                                                    | -       |
| 2.1.1.4     | Access to hazardous voltage circuit wiring                          |                                                                                                    | N/A     |
| 2.1.1.5     | Energy hazards.....:                                                | The output of the power supply presents an energy hazard. To be considered in end-use application. | N/A     |
| 2.1.1.6     | Manual controls                                                     |                                                                                                    | N/A     |
| 2.1.1.7     | Discharge of capacitors in equipment                                |                                                                                                    | Pass    |
|             | Time-constant (s); measured voltage (V).....:                       | Time constant less than 1 second.                                                                  | -       |
| 2.1.2       | Protection in service access areas                                  |                                                                                                    | N/A     |
| 2.1.3       | Protection in restricted access locations                           |                                                                                                    | N/A     |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|         |                                                                     |                                                                                                                                                                                                                                                 |      |
|---------|---------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 2.2     | <b>SELV circuits</b>                                                |                                                                                                                                                                                                                                                 | Pass |
| 2.2.1   | General requirements                                                |                                                                                                                                                                                                                                                 | Pass |
| 2.2.2   | Voltages under normal conditions (V) .....                          | All accessible voltages are less than 42.4 Vp or 60 V dc and are classified as SELV.                                                                                                                                                            | Pass |
| 2.2.3   | Voltages under fault conditions (V).....                            | Under fault conditions voltages never exceed 71V peak and 120Vdc and do not exceed 42.4V peak or 60V dc for more than 0.2 sec.                                                                                                                  | Pass |
| 2.2.3.1 | Separation by double insulation or reinforced insulation (method 1) |                                                                                                                                                                                                                                                 | Pass |
| 2.2.3.2 | Separation by earthed screen (method 2)                             |                                                                                                                                                                                                                                                 | N/A  |
| 2.2.3.3 | Protection by earthing of the SELV circuit (method 3)               |                                                                                                                                                                                                                                                 | N/A  |
| 2.2.4   | Connection of SELV circuits to other circuits.....                  | SELV circuits are only connected to other secondary circuits. SELV circuit and all interconnected circuits separated from primary by reinforced insulation. The SELV circuit does not exceed the SELV limits under normal and fault conditions. | Pass |

|       |                                                          |  |     |
|-------|----------------------------------------------------------|--|-----|
| 2.3   | <b>TNV circuits</b>                                      |  | N/A |
| 2.3.1 | Limits                                                   |  | N/A |
|       | Type of TNV circuits .....                               |  | -   |
| 2.3.2 | Separation from other circuits and from accessible parts |  | N/A |
|       | Insulation employed .....                                |  | -   |
| 2.3.3 | Separation from hazardous voltages                       |  | N/A |
|       | Insulation employed .....                                |  | -   |
| 2.3.4 | Connection of TNV circuits to other circuits             |  | N/A |
|       | Insulation employed .....                                |  | -   |
| 2.3.5 | Test for operating voltages generated externally         |  | N/A |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|       |                                                          |  |     |
|-------|----------------------------------------------------------|--|-----|
| 2.4   | <b>Limited current circuits</b>                          |  | N/A |
| 2.4.1 | General requirements                                     |  | N/A |
| 2.4.2 | Limit values                                             |  | N/A |
|       | Frequency (Hz) .....                                     |  | -   |
|       | Measured current (mA) .....                              |  | -   |
|       | Measured voltage (V) .....                               |  | -   |
|       | Measured capacitance (mF) .....                          |  | -   |
| 2.4.3 | Connection of limited current circuits to other circuits |  | N/A |

|     |                                                                                                                                                   |  |     |
|-----|---------------------------------------------------------------------------------------------------------------------------------------------------|--|-----|
| 2.5 | <b>Limited power sources</b>                                                                                                                      |  | N/A |
|     | Inherently limited output                                                                                                                         |  | N/A |
|     | Impedance limited output                                                                                                                          |  | N/A |
|     | Overcurrent protective device limited output                                                                                                      |  | N/A |
|     | Regulating network limited output under normal operating and single fault condition                                                               |  | N/A |
|     | Regulating network limited output under normal operating conditions and overcurrent protective device limited output under single fault condition |  | N/A |
|     | Output voltage (V), output current (A), apparent power (VA): .....                                                                                |  | -   |
|     | Current rating of overcurrent protective device (A):                                                                                              |  | -   |

| IEC 60950-1 |                                                                                        |                                                                                                             |         |
|-------------|----------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|---------|
| Clause      | Requirement + Test                                                                     | Result - Remark                                                                                             | Verdict |
| 2.6         | <b>Provisions for earthing and bonding</b>                                             |                                                                                                             | Pass    |
| 2.6.1       | Protective earthing                                                                    | Protective earthing provided as one level of protection against electric shock.<br>Unit is for building-in. | Pass    |
| 2.6.2       | Functional earthing                                                                    |                                                                                                             | N/A     |
| 2.6.3       | Protective earthing and protective bonding conductors                                  |                                                                                                             | Pass    |
| 2.6.3.1     | General                                                                                | Equipment shall be properly bonded over earthing terminal at chassis                                        | Pass    |
| 2.6.3.2     | Size of protective earthing conductors                                                 |                                                                                                             | N/A     |
|             | Rated current (A), cross-sectional area (mm <sup>2</sup> ), AWG .....                  |                                                                                                             | -       |
| 2.6.3.3     | Size of protective bonding conductors                                                  |                                                                                                             | N/A     |
|             | Rated current (A), cross-sectional area (mm <sup>2</sup> ), AWG .....                  |                                                                                                             | -       |
| 2.6.3.4     | Resistance (Ohm) of earthing conductors and their terminations, test current (A) ..... | 40 A                                                                                                        | Pass    |
| 2.6.3.5     | Colour of insulation .....                                                             | Only PWB traces used.                                                                                       | Pass    |
| 2.6.4       | Terminals                                                                              |                                                                                                             | Pass    |
| 2.6.4.1     | General                                                                                |                                                                                                             | Pass    |
| 2.6.4.2     | Protective earthing and bonding terminals                                              |                                                                                                             | Pass    |
|             | Rated current (A), type and nominal thread diameter (mm) .....                         | M4 used at housing.                                                                                         | -       |
| 2.6.4.3     | Separation of the protective earthing conductor from protective bonding conductors     |                                                                                                             | N/A     |
| 2.6.5       | Integrity of protective earthing                                                       |                                                                                                             | Pass    |
| 2.6.5.1     | Interconnection of equipment                                                           |                                                                                                             | N/A     |
| 2.6.5.2     | Components in protective earthing conductors and protective bonding conductors         |                                                                                                             | N/A     |
| 2.6.5.3     | Disconnection of protective earth                                                      |                                                                                                             | N/A     |
| 2.6.5.4     | Parts that can be removed by an operator                                               |                                                                                                             | N/A     |
| 2.6.5.5     | Parts removed during servicing                                                         |                                                                                                             | N/A     |
| 2.6.5.6     | Corrosion resistance                                                                   |                                                                                                             | Pass    |
| 2.6.5.7     | Screws for protective bonding                                                          |                                                                                                             | Pass    |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|         |                                                                    |  |     |
|---------|--------------------------------------------------------------------|--|-----|
| 2.6.5.8 | Reliance on telecommunication network or cable distribution system |  | N/A |
|---------|--------------------------------------------------------------------|--|-----|

|       |                                                                   |                                                      |      |
|-------|-------------------------------------------------------------------|------------------------------------------------------|------|
| 2.7   | <b>Overcurrent and earth fault protection in primary circuits</b> |                                                      | Pass |
| 2.7.1 | Basic requirements                                                |                                                      | Pass |
|       | Instructions when protection relies on building installation      |                                                      | N/A  |
| 2.7.2 | Faults not covered in 5.3                                         | The protective device is properly sized and mounted. | Pass |
| 2.7.3 | Short-circuit backup protection                                   |                                                      | Pass |
| 2.7.4 | Number and location of protective devices..... :                  | One protective device in the "LIVE" phase, F102 .    | Pass |
| 2.7.5 | Protection by several devices                                     |                                                      | N/A  |
| 2.7.6 | Warning to service personnel ..... :                              |                                                      | N/A  |

|         |                           |  |     |
|---------|---------------------------|--|-----|
| 2.8     | <b>Safety interlocks</b>  |  | N/A |
| 2.8.1   | General principles        |  | N/A |
| 2.8.2   | Protection requirements   |  | N/A |
| 2.8.3   | Inadvertent reactivation  |  | N/A |
| 2.8.4   | Fail-safe operation       |  | N/A |
| 2.8.5   | Moving parts              |  | N/A |
| 2.8.6   | Overriding                |  | N/A |
| 2.8.7   | Switches and relays       |  | N/A |
| 2.8.7.1 | Contact gaps (mm) ..... : |  | N/A |
| 2.8.7.2 | Overload test             |  | N/A |
| 2.8.7.3 | Endurance test            |  | N/A |
| 2.8.7.4 | Electric strength test    |  | N/A |
| 2.8.8   | Mechanical actuators      |  | N/A |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|       |                                    |     |      |
|-------|------------------------------------|-----|------|
| 2.9   | <b>Electrical insulation</b>       |     | Pass |
| 2.9.1 | Properties of insulating materials |     | Pass |
| 2.9.2 | Humidity conditioning              | 96h | Pass |
|       | Humidity (%) .....:                | 93  | -    |
|       | Temperature (°C).....:             | 29  | -    |
| 2.9.3 | Grade of insulation                |     | Pass |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|          |                                                                                |                                        |      |
|----------|--------------------------------------------------------------------------------|----------------------------------------|------|
| 2.10     | <b>Clearances, creepage distances and distances through insulation</b>         |                                        | Pass |
| 2.10.1   | General                                                                        |                                        | Pass |
| 2.10.2   | Determination of working voltage                                               |                                        | Pass |
| 2.10.3   | Clearances                                                                     |                                        | Pass |
| 2.10.3.1 | General                                                                        |                                        | Pass |
| 2.10.3.2 | Clearances in primary circuit                                                  |                                        | Pass |
| 2.10.3.3 | Clearances in secondary circuits                                               |                                        | Pass |
| 2.10.3.4 | Measurement of transient voltage levels                                        |                                        | N/A  |
| 2.10.4   | Creepage distances                                                             |                                        | Pass |
|          | CTI tests..... :                                                               | Material group IIIb; 100 <= CTI < 175. | -    |
| 2.10.5   | Solid insulation                                                               | certified optocoupler                  | Pass |
| 2.10.5.1 | Minimum distance through insulation                                            |                                        | Pass |
| 2.10.5.2 | Thin sheet material                                                            |                                        | Pass |
|          | Number of layers (pcs) ..... :                                                 | min. 3 layers                          | -    |
|          | Electric strength test ..... :                                                 | 3000Vac/one layer                      | -    |
| 2.10.5.3 | Printed boards                                                                 |                                        | Pass |
|          | Distance through insulation                                                    |                                        | Pass |
|          | Electric strength test for thin sheet insulating material ..... :              |                                        | -    |
|          | Number of layers (pcs) ..... :                                                 |                                        | N/A  |
| 2.10.5.4 | Wound components                                                               |                                        | N/A  |
|          | Number of layers (pcs) ..... :                                                 |                                        | N/A  |
|          | Two wires in contact inside wound component; angle between 45° and 90° ..... : |                                        | N/A  |
| 2.10.6   | Coated printed boards                                                          |                                        | N/A  |
| 2.10.6.1 | General                                                                        |                                        | N/A  |
| 2.10.6.2 | Sample preparation and preliminary inspection                                  |                                        | N/A  |
| 2.10.6.3 | Thermal cycling                                                                |                                        | N/A  |
| 2.10.6.4 | Thermal ageing (°C) ..... :                                                    |                                        | N/A  |
| 2.10.6.5 | Electric strength test ..... :                                                 |                                        | -    |



| IEC 60950-1 |                                                                  |                 |         |
|-------------|------------------------------------------------------------------|-----------------|---------|
| Clause      | Requirement + Test                                               | Result - Remark | Verdict |
| 2.10.6.6    | Abrasion resistance test                                         |                 | N/A     |
|             | Electric strength test .....                                     |                 | -       |
| 2.10.7      | Enclosed and sealed parts .....                                  |                 | N/A     |
|             | Temperature $T_1=T_2 = T_{ma} - T_{amb} + 10K (^{\circ}C)$ ..... |                 | N/A     |
| 2.10.8      | Spacings filled by insulating compound.....                      |                 | N/A     |
|             | Electric strength test .....                                     |                 | -       |
| 2.10.9      | Component external terminations                                  |                 | N/A     |
| 2.10.10     | Insulation with varying dimensions                               |                 | N/A     |

|        |                                                |                                                      |      |
|--------|------------------------------------------------|------------------------------------------------------|------|
| 3      | <b>WIRING, CONNECTIONS AND SUPPLY</b>          |                                                      | Pass |
| 3.1    | General                                        |                                                      | Pass |
| 3.1.1  | Current rating and overcurrent protection      |                                                      | Pass |
| 3.1.2  | Protection against mechanical damage           | Only PWB traces.                                     | N/A  |
| 3.1.3  | Securing of internal wiring                    |                                                      | N/A  |
| 3.1.4  | Insulation of conductors                       |                                                      | N/A  |
| 3.1.5  | Beads and ceramic insulators                   |                                                      | N/A  |
| 3.1.6  | Screws for electrical contact pressure         | Within certified terminal blocks and grounding stud. | Pass |
| 3.1.7  | Insulating materials in electrical connections |                                                      | Pass |
| 3.1.8  | Self-tapping and spaced thread screws          |                                                      | N/A  |
| 3.1.9  | Termination of conductors                      |                                                      | Pass |
|        | 10 N pull test                                 |                                                      | N/A  |
| 3.1.10 | Sleeving on wiring                             |                                                      | N/A  |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|         |                                                                        |  |     |
|---------|------------------------------------------------------------------------|--|-----|
| 3.2     | <b>Connection to an a.c. mains supply or a d.c. mains supply</b>       |  | N/A |
| 3.2.1   | Means of connection                                                    |  | N/A |
| 3.2.1.1 | Connection to an a.c. mains supply                                     |  | N/A |
| 3.2.1.2 | Connection to a d.c. mains supply                                      |  | N/A |
| 3.2.2   | Multiple supply connections                                            |  | N/A |
| 3.2.3   | Permanently connected equipment                                        |  | N/A |
|         | Number of conductors, diameter (mm) of cable and conduits..... :       |  | -   |
| 3.2.4   | Appliance inlets                                                       |  | N/A |
| 3.2.5   | Power supply cords                                                     |  | N/A |
| 3.2.5.1 | AC power supply cords                                                  |  | N/A |
|         | Type..... :                                                            |  | -   |
|         | Rated current (A), cross-sectional area (mm <sup>2</sup> ), AWG..... : |  | -   |
| 3.2.5.2 | DC power supply cords                                                  |  | N/A |
| 3.2.6   | Cord anchorages and strain relief                                      |  | N/A |
|         | Mass of equipment (kg), pull (N)..... :                                |  | -   |
|         | Longitudinal displacement (mm)..... :                                  |  | -   |
| 3.2.7   | Protection against mechanical damage                                   |  | N/A |
| 3.2.8   | Cord guards                                                            |  | N/A |
|         | D (mm); test mass (g)..... :                                           |  | -   |
|         | Radius of curvature of cord (mm)..... :                                |  | -   |
| 3.2.9   | Supply wiring space                                                    |  | N/A |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|       |                                                                                   |  |     |
|-------|-----------------------------------------------------------------------------------|--|-----|
| 3.3   | <b>Wiring terminals for connection of external conductors</b>                     |  | N/A |
| 3.3.1 | Wiring terminals                                                                  |  | N/A |
| 3.3.2 | Connection of non-detachable power supply cords                                   |  | N/A |
| 3.3.3 | Screw terminals                                                                   |  | N/A |
| 3.3.4 | Conductor sizes to be connected                                                   |  | N/A |
|       | Rated current (A), cord/cable type, cross-sectional area (mm <sup>2</sup> ) ..... |  | -   |
| 3.3.5 | Wiring terminal sizes                                                             |  | N/A |
|       | Rated current (A), type and nominal thread diameter (mm) .....                    |  | -   |
| 3.3.6 | Wiring terminals design                                                           |  | N/A |
| 3.3.7 | Grouping of wiring terminals                                                      |  | N/A |
| 3.3.8 | Stranded wire                                                                     |  | N/A |

|        |                                            |  |     |
|--------|--------------------------------------------|--|-----|
| 3.4    | <b>Disconnection from the mains supply</b> |  | N/A |
| 3.4.1  | General requirement                        |  | N/A |
| 3.4.2  | Disconnect devices                         |  | N/A |
| 3.4.3  | Permanently connected equipment            |  | N/A |
| 3.4.4  | Parts which remain energized               |  | N/A |
| 3.4.5  | Switches in flexible cords                 |  | N/A |
| 3.4.6  | Single-phase equipment and d.c. equipment  |  | N/A |
| 3.4.7  | Three-phase equipment                      |  | N/A |
| 3.4.8  | Switches as disconnect devices             |  | N/A |
| 3.4.9  | Plugs as disconnect devices                |  | N/A |
| 3.4.10 | Interconnected equipment                   |  | N/A |
| 3.4.11 | Multiple power sources                     |  | N/A |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|       |                                          |  |     |
|-------|------------------------------------------|--|-----|
| 3.5   | <b>Interconnection of equipment</b>      |  | N/A |
| 3.5.1 | General requirements                     |  | N/A |
| 3.5.2 | Types of interconnection circuits .....  |  | N/A |
| 3.5.3 | ELV circuits as interconnection circuits |  | N/A |

|     |                              |  |      |
|-----|------------------------------|--|------|
| 4   | <b>PHYSICAL REQUIREMENTS</b> |  | Pass |
| 4.1 | Stability                    |  | N/A  |
|     | Angle of 10°                 |  | N/A  |
|     | Test: force (N) .....        |  | N/A  |

|        |                                                    |                     |      |
|--------|----------------------------------------------------|---------------------|------|
| 4.2    | <b>Mechanical strength</b>                         |                     | Pass |
| 4.2.1  | General                                            |                     | Pass |
| 4.2.2  | Steady force test, 10 N                            |                     | N/A  |
| 4.2.3  | Steady force test, 30 N                            | Done by inspection. | Pass |
| 4.2.4  | Steady force test, 250 N                           |                     | N/A  |
| 4.2.5  | Impact test                                        |                     | N/A  |
|        | Fall test                                          |                     | N/A  |
|        | Swing test                                         |                     | N/A  |
| 4.2.6  | Drop test                                          |                     | N/A  |
| 4.2.7  | Stress relief test                                 |                     | N/A  |
| 4.2.8  | Cathode ray tubes                                  |                     | N/A  |
|        | Picture tube separately certified .....            |                     | N/A  |
| 4.2.9  | High pressure lamps                                |                     | N/A  |
| 4.2.10 | Wall or ceiling mounted equipment; force (N) ..... |                     | N/A  |

| IEC 60950-1 |                                                                                    |                              |         |
|-------------|------------------------------------------------------------------------------------|------------------------------|---------|
| Clause      | Requirement + Test                                                                 | Result - Remark              | Verdict |
| 4.3         | <b>Design and construction</b>                                                     |                              | Pass    |
| 4.3.1       | Edges and corners                                                                  |                              | Pass    |
| 4.3.2       | Handles and manual controls; force (N) .....                                       |                              | N/A     |
| 4.3.3       | Adjustable controls                                                                | No user adjustable controls. | N/A     |
| 4.3.4       | Securing of parts                                                                  |                              | N/A     |
| 4.3.5       | Connection of plugs and sockets                                                    |                              | N/A     |
| 4.3.6       | Direct plug-in equipment                                                           |                              | N/A     |
|             | Dimensions (mm) of mains plug for direct plug-in . :                               |                              | N/A     |
|             | Torque and pull test of mains plug for direct plug-in; torque (Nm); pull (N) ..... |                              | N/A     |
| 4.3.7       | Heating elements in earthed equipment                                              |                              | N/A     |
| 4.3.8       | Batteries                                                                          |                              | N/A     |
| 4.3.9       | Oil and grease                                                                     |                              | N/A     |
| 4.3.10      | Dust, powders, liquids and gases                                                   |                              | N/A     |
| 4.3.11      | Containers for liquids or gases                                                    |                              | N/A     |
| 4.3.12      | Flammable liquids .....                                                            |                              | N/A     |
|             | Quantity of liquid (l) .....                                                       |                              | N/A     |
|             | Flash point (°C) .....                                                             |                              | N/A     |
| 4.3.13      | Radiation; type of radiation                                                       |                              | Pass    |
| 4.3.13.1    | General                                                                            |                              | N/A     |
| 4.3.13.2    | Ionizing radiation                                                                 |                              | N/A     |
|             | Measured radiation (pA/kg) .....                                                   |                              | -       |
|             | Measured high-voltage (kV) .....                                                   |                              | -       |
|             | Measured focus voltage (kV) .....                                                  |                              | -       |
|             | CRT markings .....                                                                 |                              | -       |
| 4.3.13.3    | Effect of ultraviolet (UV) radiation on materials                                  |                              | N/A     |
|             | Part, property, retention after test, flammability classification .....            |                              | N/A     |
| 4.3.13.4    | Human exposure to ultraviolet (UV) radiation .....                                 |                              | N/A     |
| 4.3.13.5    | Laser (including LEDs)                                                             | Only indication LEDs used.   | Pass    |
|             | Laser class .....                                                                  |                              | -       |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|          |                   |  |     |
|----------|-------------------|--|-----|
| 4.3.13.6 | Other types ..... |  | N/A |
|----------|-------------------|--|-----|

|       |                                                  |  |     |
|-------|--------------------------------------------------|--|-----|
| 4.4   | <b>Protection against hazardous moving parts</b> |  | N/A |
| 4.4.1 | General                                          |  | N/A |
| 4.4.2 | Protection in operator access areas              |  | N/A |
| 4.4.3 | Protection in restricted access locations        |  | N/A |
| 4.4.4 | Protection in service access areas               |  | N/A |

|       |                                         |                                                                                                                                                     |      |
|-------|-----------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|------|
| 4.5   | <b>Thermal requirements</b>             |                                                                                                                                                     | Pass |
| 4.5.1 | Maximum temperatures                    |                                                                                                                                                     | Pass |
|       | Normal load condition per Annex L ..... | Operated in the most unfavorable way of operation given in the operating instructions until steady conditions established.                          | N/A  |
| 4.5.2 | Resistance to abnormal heat             | It has been determined from examination of the physical characteristics of the materials used that the material meets the requirements of the test. | Pass |

|       |                                                  |                                                                                              |     |
|-------|--------------------------------------------------|----------------------------------------------------------------------------------------------|-----|
| 4.6   | <b>Openings in enclosures</b>                    |                                                                                              | N/A |
| 4.6.1 | Top and side openings                            | Appropriate electrical and fire enclosure needs to be considered in the end use application. | N/A |
|       | Dimensions (mm).....                             |                                                                                              | -   |
| 4.6.2 | Bottoms of fire enclosures                       |                                                                                              | N/A |
|       | Construction of the bottom.....                  |                                                                                              | -   |
| 4.6.3 | Doors or covers in fire enclosures               |                                                                                              | N/A |
| 4.6.4 | Openings in transportable equipment              |                                                                                              | N/A |
| 4.6.5 | Adhesives for constructional purposes            |                                                                                              | N/A |
|       | Conditioning temperature (°C)/time (weeks) ..... |                                                                                              | -   |

| IEC 60950-1 |                                                                        |                                                                                             |         |
|-------------|------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|---------|
| Clause      | Requirement + Test                                                     | Result - Remark                                                                             | Verdict |
| 4.7         | <b>Resistance to fire</b>                                              |                                                                                             | Pass    |
| 4.7.1       | Reducing the risk of ignition and spread of flame                      |                                                                                             | Pass    |
|             | Method 1, selection and application of components wiring and materials |                                                                                             | Pass    |
|             | Method 2, application of all of simulated fault condition tests        |                                                                                             | N/A     |
| 4.7.2       | Conditions for a fire enclosure                                        | To be considered in the end application.                                                    | N/A     |
| 4.7.2.1     | Parts requiring a fire enclosure                                       |                                                                                             | Pass    |
| 4.7.2.2     | Parts not requiring a fire enclosure                                   |                                                                                             | N/A     |
| 4.7.3       | Materials                                                              |                                                                                             | Pass    |
| 4.7.3.1     | General                                                                |                                                                                             | Pass    |
| 4.7.3.2     | Materials for fire enclosures                                          |                                                                                             | N/A     |
| 4.7.3.3     | Materials for components and other parts outside fire enclosures       |                                                                                             | N/A     |
| 4.7.3.4     | Materials for components and other parts inside fire enclosures        | All internal materials are rated V-2 or better or are mounted on a PWB rated V-1 or better. | Pass    |
| 4.7.3.5     | Materials for air filter assemblies                                    |                                                                                             | N/A     |
| 4.7.3.6     | Materials used in high-voltage components                              |                                                                                             | N/A     |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|         |                                                                                                                          |                                                        |      |
|---------|--------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|------|
| 5       | <b>ELECTRICAL REQUIREMENTS AND SIMULATED ABNORMAL CONDITIONS</b>                                                         |                                                        | Pass |
| 5.1     | Touch current and protective conductor current                                                                           |                                                        | Pass |
| 5.1.1   | General                                                                                                                  |                                                        | Pass |
| 5.1.2   | Equipment under test (EUT)                                                                                               |                                                        | Pass |
| 5.1.3   | Test circuit                                                                                                             |                                                        | Pass |
| 5.1.4   | Application of measuring instrument                                                                                      |                                                        | Pass |
| 5.1.5   | Test procedure                                                                                                           |                                                        | Pass |
| 5.1.6   | Test measurements                                                                                                        |                                                        | Pass |
|         | Test voltage (V) .....                                                                                                   | 264Vac, 50Hz;                                          | -    |
|         | Measured touch current (mA) .....                                                                                        | Max. 0.508mA at housing;<br>max. 0.008mA at Plus/Minus | -    |
|         | Max. allowed touch current (mA) .....                                                                                    | 3.5mA                                                  | -    |
|         | Measured protective conductor current (mA) .....                                                                         | -                                                      | -    |
|         | Max. allowed protective conductor current (mA) ...                                                                       | -                                                      | -    |
| 5.1.7   | Equipment with touch current exceeding 3.5 mA ..                                                                         |                                                        | N/A  |
| 5.1.8   | Touch currents to and from telecommunication networks and cable distribution systems and from telecommunication networks |                                                        | N/A  |
| 5.1.8.1 | Limitation of the touch current to a telecommunication network and a cable distribution system                           |                                                        | N/A  |
|         | Test voltage (V) .....                                                                                                   |                                                        | -    |
|         | Measured touch current (mA) .....                                                                                        |                                                        | -    |
|         | Max. allowed touch current (mA) .....                                                                                    |                                                        | -    |
| 5.1.8.2 | Summation of touch currents from telecommunication networks .....                                                        |                                                        | N/A  |

|       |                          |  |      |
|-------|--------------------------|--|------|
| 5.2   | <b>Electric strength</b> |  | Pass |
| 5.2.1 | General                  |  | Pass |
| 5.2.2 | Test procedure           |  | Pass |



| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|       |                                                                 |                                                                        |      |
|-------|-----------------------------------------------------------------|------------------------------------------------------------------------|------|
| 5.3   | <b>Abnormal operating and fault conditions</b>                  |                                                                        | Pass |
| 5.3.1 | Protection against overload and abnormal operation              |                                                                        | Pass |
| 5.3.2 | Motors                                                          |                                                                        | N/A  |
| 5.3.3 | Transformers                                                    |                                                                        | Pass |
| 5.3.4 | Functional insulation .....                                     | Functional insulation complies with the requirements (a), (b), or (c). | Pass |
| 5.3.5 | Electromechanical components                                    |                                                                        | N/A  |
| 5.3.6 | Simulation of faults                                            |                                                                        | Pass |
| 5.3.7 | Unattended equipment                                            |                                                                        | N/A  |
| 5.3.8 | Compliance criteria for abnormal operating and fault conditions |                                                                        | Pass |

|         |                                                                                                                                               |  |     |
|---------|-----------------------------------------------------------------------------------------------------------------------------------------------|--|-----|
| 6       | <b>CONNECTION TO TELECOMMUNICATION NETWORKS</b>                                                                                               |  | N/A |
| 6.1     | Protection of telecommunication network service persons, and users of other equipment connected to the network, from hazards in the equipment |  | N/A |
| 6.1.1   | Protection from hazardous voltages                                                                                                            |  | N/A |
| 6.1.2   | Separation of the telecommunication network from earth                                                                                        |  | N/A |
| 6.1.2.1 | Requirements                                                                                                                                  |  | N/A |
|         | Test voltage (V) .....                                                                                                                        |  | -   |
|         | Current in the test circuit (mA) .....                                                                                                        |  | -   |
| 6.1.2.2 | Exclusions .....                                                                                                                              |  | N/A |

|         |                                                                                      |  |     |
|---------|--------------------------------------------------------------------------------------|--|-----|
| 6.2     | <b>Protection of equipment users from overvoltages on telecommunication networks</b> |  | N/A |
| 6.2.1   | Separation requirements                                                              |  | N/A |
| 6.2.2   | Electric strength test procedure                                                     |  | N/A |
| 6.2.2.1 | Impulse test                                                                         |  | N/A |
| 6.2.2.2 | Steady-state test                                                                    |  | N/A |
| 6.2.2.3 | Compliance criteria                                                                  |  | N/A |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|     |                                                                           |  |     |
|-----|---------------------------------------------------------------------------|--|-----|
| 6.3 | <b>Protection of the telecommunication wiring system from overheating</b> |  | N/A |
|     | Max. output current (A).....:                                             |  | -   |
|     | Current limiting method.....:                                             |  | -   |

|       |                                                                                                                                                         |  |     |
|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------|--|-----|
| 7     | <b>CONNECTION TO CABLE DISTRIBUTION SYSTEMS</b>                                                                                                         |  | N/A |
| 7.1   | Protection of cable distribution system service persons, and users of other equipment connected to the system, from hazardous voltages in the equipment |  | N/A |
| 7.2   | Protection of equipment users from overvoltages on the cable distribution system                                                                        |  | N/A |
| 7.3   | Insulation between primary circuits and cable distribution systems                                                                                      |  | N/A |
| 7.3.1 | General                                                                                                                                                 |  | N/A |
| 7.3.2 | Voltage surge test                                                                                                                                      |  | N/A |
| 7.3.3 | Impulse test                                                                                                                                            |  | N/A |

|       |                                                                                                                                           |  |     |
|-------|-------------------------------------------------------------------------------------------------------------------------------------------|--|-----|
| A     | <b>Annex A, TESTS FOR RESISTANCE TO HEAT AND FIRE</b>                                                                                     |  | N/A |
| A.1   | Flammability test for fire enclosures of movable equipment having a total mass exceeding 18 kg, and of stationary equipment (see 4.7.3.2) |  | N/A |
| A.1.1 | Samples.....:                                                                                                                             |  | -   |
|       | Wall thickness (mm).....:                                                                                                                 |  | -   |
| A.1.2 | Conditioning of samples; temperature (°C).....:                                                                                           |  | N/A |
| A.1.3 | Mounting of samples.....:                                                                                                                 |  | N/A |
| A.1.4 | Test flame                                                                                                                                |  | N/A |
| A.1.5 | Test procedure                                                                                                                            |  | N/A |
| A.1.6 | Compliance criteria                                                                                                                       |  | N/A |
|       | Sample 1 burning time (s).....:                                                                                                           |  | -   |
|       | Sample 2 burning time (s).....:                                                                                                           |  | -   |
|       | Sample 3 burning time (s).....:                                                                                                           |  | -   |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|       |                                                                                                                                                                                                     |  |     |
|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-----|
| A.2   | <b>Flammability test for fire enclosures of movable equipment having a total mass not exceeding 18 kg, and for material and components located inside fire enclosures (see 4.7.3.2 and 4.7.3.4)</b> |  | N/A |
| A.2.1 | Samples, material .....                                                                                                                                                                             |  | -   |
|       | Wall thickness (mm) .....                                                                                                                                                                           |  | -   |
| A.2.2 | Conditioning of samples                                                                                                                                                                             |  | N/A |
| A.2.3 | Mounting of samples                                                                                                                                                                                 |  | N/A |
| A.2.4 | Test flame                                                                                                                                                                                          |  | N/A |
| A.2.5 | Test procedure                                                                                                                                                                                      |  | N/A |
| A.2.6 | Compliance criteria                                                                                                                                                                                 |  | N/A |
|       | Sample 1 burning time (s).....                                                                                                                                                                      |  | -   |
|       | Sample 2 burning time (s).....                                                                                                                                                                      |  | -   |
|       | Sample 3 burning time (s).....                                                                                                                                                                      |  | -   |
| A.2.7 | Alternative test acc. to IEC 60695-2-2, cl. 4, 8                                                                                                                                                    |  | N/A |
|       | Sample 1 burning time (s).....                                                                                                                                                                      |  | -   |
|       | Sample 2 burning time (s).....                                                                                                                                                                      |  | -   |
|       | Sample 3 burning time (s).....                                                                                                                                                                      |  | -   |

|       |                                         |  |     |
|-------|-----------------------------------------|--|-----|
| A.3   | <b>Hot flaming oil test (see 4.6.2)</b> |  | N/A |
| A.3.1 | Mounting of samples                     |  | N/A |
| A.3.2 | Test procedure                          |  | N/A |
| A.3.3 | Compliance criterion                    |  | N/A |

| IEC 60950-1 |                                                                              |                 |         |
|-------------|------------------------------------------------------------------------------|-----------------|---------|
| Clause      | Requirement + Test                                                           | Result - Remark | Verdict |
| B           | <b>Annex B, MOTOR TESTS UNDER ABNORMAL CONDITIONS(see 4.7.2.2 and 5.3.2)</b> |                 | N/A     |
| B.1         | General requirements                                                         |                 | N/A     |
|             | Position .....                                                               |                 | -       |
|             | Manufacturer .....                                                           |                 | -       |
|             | Type .....                                                                   |                 | -       |
|             | Rated values .....                                                           |                 | -       |
| B.2         | Test conditions                                                              |                 | N/A     |
| B.3         | Maximum temperatures                                                         |                 | N/A     |
| B.4         | Running overload test                                                        |                 | N/A     |
| B.5         | Locked-rotor overload test                                                   |                 | N/A     |
|             | Test duration (days) .....                                                   |                 | -       |
|             | Electric strength test: test voltage (V) .....                               |                 | -       |
| B.6         | Running overload test for d.c. motors in secondary circuits                  |                 | N/A     |
| B.7         | Locked-rotor overload test for d.c. motors in secondary circuits             |                 | N/A     |
| B.7.1       | Test procedure                                                               |                 | N/A     |
| B.7.2       | Alternative test procedure; test time (h) .....                              |                 | N/A     |
| B.7.3       | Electric strength test                                                       |                 | N/A     |
| B.8         | Test for motors with capacitors                                              |                 | N/A     |
| B.9         | Test for three-phase motors                                                  |                 | N/A     |
| B.10        | Test for series motors                                                       |                 | N/A     |
|             | Operating voltage (V) .....                                                  |                 | -       |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|     |                                                    |                                                              |      |
|-----|----------------------------------------------------|--------------------------------------------------------------|------|
| C   | <b>Annex C, TRANSFORMERS (see 1.5.4 and 5.3.3)</b> |                                                              | Pass |
|     | Position .....                                     | T1                                                           | -    |
|     | Manufacturer .....                                 | PULS GmbH                                                    | -    |
|     | Type .....                                         | TE-360.590.00 for 24V model,<br>TE-360.595.05 for 48V model. | -    |
|     | Rated values .....                                 | -                                                            | -    |
|     | Method of protection .....                         | Impedance                                                    | -    |
| C.1 | Overload test                                      | Max. 132°C measured at 23°C ambient;                         | Pass |
| C.2 | Insulation                                         |                                                              | Pass |
|     | Protection from displacement of windings .....     | Margin tape provided on each end of each winding.            | Pass |

|     |                                                               |  |      |
|-----|---------------------------------------------------------------|--|------|
| D   | <b>Annex D, MEASURING INSTRUMENTS FOR TOUCH-CURRENT TESTS</b> |  | Pass |
| D.1 | Measuring instrument                                          |  | Pass |
| D.2 | Alternative measuring instrument                              |  | N/A  |

|   |                                               |  |      |
|---|-----------------------------------------------|--|------|
| E | <b>Annex E, TEMPERATURE RISE OF A WINDING</b> |  | Pass |
|---|-----------------------------------------------|--|------|

|   |                                                                             |  |      |
|---|-----------------------------------------------------------------------------|--|------|
| F | <b>Annex F, MEASUREMENT OF CLEARANCES AND CREEPAGE DISTANCES (see 2.10)</b> |  | Pass |
|---|-----------------------------------------------------------------------------|--|------|

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|       |                                                                           |  |     |
|-------|---------------------------------------------------------------------------|--|-----|
| G     | <b>Annex G, ALTERNATIVE METHOD FOR DETERMINING MINIMUM CLEARANCES</b>     |  | N/A |
| G.1   | Summary of the procedure for determining minimum clearances               |  | N/A |
| G.2   | Determination of mains transient voltage (V)                              |  | N/A |
| G.2.1 | AC mains supply                                                           |  | N/A |
| G.2.2 | DC mains supply                                                           |  | N/A |
| G.3   | Determination of telecommunication network transient voltage (V) :..... : |  | N/A |
| G.4   | Determination of required withstand voltage (V) ... :                     |  | N/A |
| G.5   | Measurement of transient levels (V)..... :                                |  | N/A |
| G.6   | Determination of minimum clearances ..... :                               |  | N/A |

|   |                                                 |  |     |
|---|-------------------------------------------------|--|-----|
| H | <b>ANNEX H, IONIZING RADIATION (see 4.3.13)</b> |  | N/A |
|---|-------------------------------------------------|--|-----|

|   |                                                                   |                       |      |
|---|-------------------------------------------------------------------|-----------------------|------|
| J | <b>Annex J, TABLE OF ELECTROCHEMICAL POTENTIALS (see 2.6.5.6)</b> |                       | Pass |
|   | Metal used ..... :                                                | Aluminium/Zinc alloy. | -    |

|     |                                                              |  |     |
|-----|--------------------------------------------------------------|--|-----|
| K   | <b>ANNEX K, THERMAL CONTROLS (see 1.5.3 and 5.3.7)</b>       |  | N/A |
| K.1 | Making and breaking capacity                                 |  | N/A |
| K.2 | Thermostat reliability; operating voltage (V) ..... :        |  | N/A |
| K.3 | Thermostat endurance test; operating voltage (V) :           |  | N/A |
| K.4 | Temperature limiter endurance; operating voltage (V) ..... : |  | N/A |
| K.5 | Thermal cut-out reliability                                  |  | N/A |
| K.6 | Stability of operation                                       |  | N/A |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|     |                                                                                                                |                           |      |
|-----|----------------------------------------------------------------------------------------------------------------|---------------------------|------|
| L   | <b>Annex L, NORMAL LOAD CONDITIONS FOR SOME TYPES OF ELECTRICAL BUSINESS EQUIPMENT (see 1.2.2.1 and 4.5.1)</b> |                           | Pass |
| L.1 | Typewriters                                                                                                    |                           | N/A  |
| L.2 | Adding machines and cash registers                                                                             |                           | N/A  |
| L.3 | Erasers                                                                                                        |                           | N/A  |
| L.4 | Pencil sharpeners                                                                                              |                           | N/A  |
| L.5 | Duplicators and copy machines                                                                                  |                           | N/A  |
| L.6 | Motor-operated files                                                                                           |                           | N/A  |
| L.7 | Other business equipment                                                                                       | Refer to GPI for details. | Pass |

|         |                                                                    |  |     |
|---------|--------------------------------------------------------------------|--|-----|
| M       | <b>Annex M, CRITERIA FOR TELEPHONE RINGING SIGNALS (see 2.3.1)</b> |  | N/A |
| M.1     | Introduction                                                       |  | N/A |
| M.2     | Method A                                                           |  | N/A |
| M.3     | Method B                                                           |  | N/A |
| M.3.1   | Ringing signal                                                     |  | N/A |
| M.3.1.1 | Frequency (Hz) .....                                               |  | -   |
| M.3.1.2 | Voltage (V) .....                                                  |  | -   |
| M.3.1.3 | Cadence; time (s), voltage (V) .....                               |  | -   |
| M.3.1.4 | Single fault current (mA) .....                                    |  | -   |
| M.3.2   | Tripping device and monitoring voltage .....                       |  | N/A |
| M.3.2.1 | Conditions for use of a tripping device or a monitoring voltage    |  | N/A |
| M.3.2.2 | Tripping device                                                    |  | N/A |
| M.3.2.3 | Monitoring voltage (V) .....                                       |  | N/A |

|     |                                                                                       |  |     |
|-----|---------------------------------------------------------------------------------------|--|-----|
| N   | <b>Annex N, IMPULSE TEST GENERATORS (see 2.10.3.4, 6.2.2.1, 7.3.2 and clause G.5)</b> |  | N/A |
| N.1 | ITU-T impulse test generators                                                         |  | N/A |
| N.2 | IEC 60065 impulse test generator                                                      |  | N/A |

| IEC 60950-1 |                    |                 |         |
|-------------|--------------------|-----------------|---------|
| Clause      | Requirement + Test | Result - Remark | Verdict |

|   |                                      |  |      |
|---|--------------------------------------|--|------|
| P | <b>Annex P, NORMATIVE REFERENCES</b> |  | Pass |
|---|--------------------------------------|--|------|

|   |                              |  |      |
|---|------------------------------|--|------|
| Q | <b>Annex Q, BIBLIOGRAPHY</b> |  | Pass |
|---|------------------------------|--|------|

|     |                                                                                 |  |     |
|-----|---------------------------------------------------------------------------------|--|-----|
| R   | <b>Annex R, EXAMPLES OF REQUIREMENTS FOR QUALITY CONTROL PROGRAMMES</b>         |  | N/A |
| R.1 | Minimum separation distances for unpopulated coated printed boards (see 2.10.6) |  | N/A |
| R.2 | Reduced clearances (see 2.10.3)                                                 |  | N/A |

|     |                                                             |  |     |
|-----|-------------------------------------------------------------|--|-----|
| S   | <b>Annex S, PROCEDURE FOR IMPULSE TESTING (see 6.2.2.3)</b> |  | N/A |
| S.1 | Test equipment                                              |  | N/A |
| S.2 | Test procedure                                              |  | N/A |
| S.3 | Examples of waveforms during impulse testing                |  | N/A |

|   |                                                                             |  |     |
|---|-----------------------------------------------------------------------------|--|-----|
| T | <b>Annex T, GUIDANCE ON PROTECTION AGAINST INGRESS OF WATER (see 1.1.2)</b> |  | N/A |
|   | ..... :                                                                     |  | -   |

|   |                                                                                               |  |     |
|---|-----------------------------------------------------------------------------------------------|--|-----|
| U | <b>Annex U, INSULATED WINDING WIRES FOR USE WITHOUT INTERLEAVED INSULATION (see 2.10.5.4)</b> |  | N/A |
|   | ..... :                                                                                       |  | -   |



*This is an extract of the CB-Scheme report with the most important information.  
If a complete copy of the report is required, please contact your PULS sales representative.*