

## 02-164F Series

From 1.0  $\mu\text{H}$  to 1000  $\mu\text{H}$



### CHARACTERISTICS

- Description:** SMD power inductor.
- Applications:** Ideal for a variety of DC/DC converter applications and low profile use.
- Operating Temperature:** -30°C to +100°C
- Inductance Tolerance:**  $\pm 10\%$ ,  $\pm 20\%$
- Testing:** Inductance is tested on an HP4285A at 100KHz.
- Packaging:** Tape & Reel.
- Marking:** Parts are marked with inductance code.
- Miscellaneous:** RoHS Compliant.
- Additional Information:** Additional electrical & physical information available upon request.
- Samples available. See website for ordering information.**

### SPECIFICATIONS

Part numbers are marked to indicate tolerance available.  
K =  $\pm 10\%$ , M =  $\pm 20\%$

Part Number	Inductance ( $\mu\text{H}$ )	L Test Freq. (KHz)	DCR Max. ( $\Omega$ )	Rated DC (A)
02-164F-1R0M	1.0	100	0.023	2.880
02-164F-1R5M	1.5	100	0.028	2.560
02-164F-2R2M	2.2	100	0.032	2.360
02-164F-2R7M	2.7	100	0.035	2.360
02-164F-3R3M	3.3	100	0.038	2.160
02-164F-3R9M	3.9	100	0.042	2.160
02-164F-4R7M	4.7	100	0.049	1.880
02-164F-5R6M	5.6	100	0.055	1.880
02-164F-6R8M	6.8	100	0.055	1.880
02-164F-8R2M	8.2	100	0.067	1.680
02-164F-100M	10	100	0.070	1.560
02-164F-120M	12	100	0.080	1.440
02-164F-150M	15	100	0.090	1.360
02-164F-180M	18	100	0.100	1.280
02-164F-220M	22	100	0.120	1.170
02-164F-270M	27	100	0.140	1.070
02-164F-330M	33	100	0.160	1.000
02-164F-390M	39	100	0.190	0.910
02-164F-470M	47	100	0.220	0.840
02-164F-560M	56	100	0.290	0.720
02-164F-680M	68	100	0.340	0.660
02-164F-820M	82	100	0.460	0.580
02-164F-101M	100	100	0.550	0.510
02-164F-121K	120	100	0.670	0.420
02-164F-151K	150	100	0.900	0.370
02-164F-181K	180	100	1.050	0.350
02-164F-221K	220	100	1.350	0.290
02-164F-271K	270	100	1.550	0.280
02-164F-331K	330	100	2.050	0.230
02-164F-391K	390	100	2.300	0.215
02-164F-471K	470	100	2.600	0.195
02-164F-561M	560	100	2.900	0.185
02-164F-681M	680	100	3.400	0.170
02-164F-821M	820	100	4.200	0.165
02-164F-102M	1000	100	5.390	0.150

### PHYSICAL DIMENSIONS

Size	A Max.	B Max.	C Max.	D	E Max.
mm	7.4	7.4	5.5	2.0 $\pm$ 0.2	5.4
inches	0.29	0.29	0.22	0.08 $\pm$ 0.008	0.21

