

UI series U3913 - 18VA

- Safety transformers according to the European standard CEI EN 61558-1 and CEI EN 61558-2-6
- Primary and Secondary two chamber windings
- Epoxy encapsulated
- Marking on primary side
- Tin-plated phosphor bronze pins
- Pins size: $\varnothing 0,9$ mm typ , length 4mm min
- Only electrically used pins are mounted
- 5000V dielectric strength between primary and secondary windings
- 100% tested
- Custom versions on request
- Fixing with 4 self-tapping screws 3x16mm



18 VA - t_a50/B



Code	Primary (50-60Hz)	Secondary ¹	Output fuses ²
U3913S06	2x115V	2x 6V - 1500 mA	2 fuses 1600 mA
U3913S09	2x115V	2x 9V - 1000 mA	2 fuses 1000 mA
U3913S12	2x115V	2x 12V - 750 mA	2 fuses 800 mA
U3913S15	2x115V	2x 15V - 600 mA	2 fuses 630 mA
U3913S18	2x115V	2x 18V - 500 mA	2 fuses 500 mA

Dimensions	mm	Layout (bottom view)	Dimensions	.stp file Download
a max	68,6			
b max	57,7			
h max	28,2			
x typ	5,0			
x1 typ	6,0			
y typ	45,0			
c typ	62,6			
d typ	50,2			

230V / 2xVsec	230V / 2xIsec	115V / 2xVsec	115V / 2xIsec
Primary double voltage Secondary double voltage	Primary double voltage Secondary double current	Primary double current Secondary double voltage	Primary double current Secondary double current

¹ Rated voltage (No load voltage x 1,28).

² See the output fuses notes on back cover. Different overload protection are possible if the user performs proper tests to assure the relevant standard compliance.