

Murata PLA10AS1030R7R2B alternative

2 Line Common Mode Choke Through Hole 700mA DCR 860mOhm



Part Number UU10.5LF-102-CM

SPECIFICATION APPROVAL

CUSTOMER : BEC Distribution



PRODUCT : UU10.5LF-102-CM

Pb-free

CODE NO. : C05110014

CUS. CODE :

SPEC.NO. : C-5110-014(02)

DATE : 2-Mar-05

CUSTOMER APPROVAL

BEC DISTRIBUTION Ltd.

www.bec.co.uk

email: sales@bec.co.uk


Phone: +44(0)1844 275824

PREPARED BY	APPROVED BY	AUTHORIZED BY
JEAN	TONY	MASCOT

Murata PLA10AS1030R7R2B alternative

PRODUCT	UU10.5LF-102-CM	COIL SPECIFICATION	DATE	2005/3/2
SPEC.NO.	C-5110-014(02)		CODE NO.	C05110014

EXTERNAL DIMENSIONS :



A	: 19.0 Max.	m/m
B	: 17.0 Max.	m/m
C	: 4.0±1.0	m/m
D	: 22.0 Max.	m/m
E	: 0.7±0.1	m/m
F	: 13.0±0.5	m/m
G	: 10.0±0.5	m/m

ELECTRICAL CHARACTERISTIC :


L(mH) : 1.0 Min. 1KHz 0.25V

DCR(mΩ) : 120 Max.

IDC(A) : 2.0 Max.

Hipot : 1500V/AC 5mA 2sec, winding to winding and Winding to cores.

SCHEMATIC DRAWING :



MATERIAL LIST :

NO	ITEM	MATERIAL	SUPPLIER OF THE MATERIAL
1	CORE	Ferrite Core	ACME or EQU
2	WIRE	P155 Cooper Wire	Pacific or EQU
3			
4			
5			

Murata PLA10AS1030R7R2B alternative



PRODUCT	UU10.5LF-102-CM	COIL SPECIFICATION	DATE	2005/3/2
SPEC.NO.	C-5110-014(02)		CODE NO.	C05110014


TEST DATA

ELECTRICAL CHARACTERISTICS								
MEAS. ITEM	L1(mH)	L2(mH)	DCR1(mΩ)	DCR2(mΩ)				
TEST FREQ.	1KHz 0.25V	1KHz 0.25V	Max.	Max.				
YOUR								
SPEC.	1.0 Min.	1.0 Min.	120	120				
1								
2								
3								
4								
5								
6								
7								
8								
9								
10								
X	#DIV/0!	#DIV/0!	#DIV/0!	#DIV/0!				
R	0.00	0.00	0.00	0.00				

DIMENSION								
MEAS. ITEM	A	B	C	D	E	F	G	
TEST FREQ.	m/m	m/m	m/m	m/m	m/m	m/m	m/m	
YOUR								
SPEC.	19.0 Max.	17.0 Max.	4.0±1.0	22.0 Max.	0.7±0.1	13.0±0.5	10.0±0.5	
1								
2								
3								
4								
5								
6								
7								
8								
9								
10								
X	#DIV/0!	#DIV/0!	#DIV/0!	#DIV/0!	#DIV/0!	#DIV/0!	#DIV/0!	
R	0.00	0.00	0.00	0.00	0.00	0.00	0.00	

Murata PLA10AS1030R7R2B alternative



PRODUCT	UU10.5LF-102-CM	COIL SPECIFICATION	DATE	2005/3/2
SPEC.NO.	C-5110-014(02)		CODE NO.	C05110014
TEST ITEMS	SPECIFICATIONS	TEST CONDITIONS / TEST METHODS		
<u>ELECTRICAL PERFORMANCE TEST</u>				
L	REFER TO STANDARD ELECTRICAL CHARACTERISTIC LIST.	CH-1061 OR EQUIV.		
DCR		CH-502A OR EQUIV		
RATED CURRENT		APPLIED THE CURRENT TO COILS THE INDUCTANCE CHANGE SHOULD BE LESS THAN 10% TO INITIAL VALUE AND TEMPERATURE RISE SHOULD NOT BE MORE THAN 40°C..		
TEMPERATURE RISE TEST	40°C MAX (Δt)	1. APPLIED THE ALLOWED DC CURRENT FOR 4 HOURS 2. TEMPERATURE MEASURE BY DIGITAL SURFACE THERMOMETER.		
OVER LOAD TEST	NO EVIDENCE OF ELECTRICAL DAMAGE	APPLIED 1.5 TIMES OF RATED ALLOWED DC CURRENT TO INDUCTORS FOR A PERIOD OF 5 MINUTES.		
<u>MECHANICAL PERFORMANCE TEST</u>				
SOLDER HEAT RESISTANCE	1. INDUCTORS SHOULD HAVE NO EVIDENCE OF ELECTRICAL AND MECHANICAL DAMAGE 2. INDUCTANCE SHOULD NOT CHANGE MORE THAN $\pm 10\%$ 3. SOLDER MATERIAL WILL BE LEAD FREE.	PREHEAT: 150°C 60SECS		
		SOLDER TEMPERATURE: 255 \pm 5°C		
		FLUX: ROXIN.. DIP TIME: 10 \pm 0.5SECS. 		
VIBRATION TEST (LOW FREQUENCY)		1.AMPLITUDE: 1.5 mm 2.FREQUENCY: 10-55-10HZ / 1 MIN 3.DIRECTION: X, Y, Z 4.DURATION: 2 HRS/X, Y, Z		
SHOCK TEST		INDUCTORS SHOULD BE DROPPED 10 TIMES FROM A HEIGHT OF 1m ONTO 3cm WOODEN BOARD.		

Murata PLA10AS1030R7R2B alternative



PRODUCT	UU10.5LF-102-CM	COIL SPECIFICATION	DATE	2005/3/2
SPEC.NO.	C-5110-014(02)		CODE NO.	C05110014

TEST ITEMS	SPECIFICATIONS	TEST CONDITIONS / TEST METHODS
------------	----------------	--------------------------------

CLIMATIC TEST

TEMPERATURE CHARACTERISTIC	1.APPEARANCE:NO DAMAGE 2.INDUCTANCE:WITHIN±10% OF INITIAL VALUE.	- 40°C ~ +85°C	
HUMIDITY TEST		60°C±2°C / 96±2 HOURS	
LOW TEMPERATURE STORAGE		1.TEMPERATURE:- 25°C±2°C 2.TIME: 96±2 HOURS	
THERMAL SHOCK TEST		1.-25±5°C FOR 30 MINUTES. +80±5°C FOR 30 MINUTES. 2.TOTAL: 10 CYCLES	
HIGH TEMPERATURE STORAGE		1.APPLIED CURRENT: MAX RATED CURRENT 2.TEMPERATURE:80°C±2°C	

NOTE : INDUCTORS ARE TO BE TESTED AFTER 2 HOUR AT ROOM TEMPERATURE.

LIFE TEST

HIGH TEMPERATURE LOAD LIFE TEST	INDUCTORS SHOULD BE NO EVIDENCE OF SHORT OR OPEN CIRCUIT	1. TEMPERATURE: 80±2°C 2. TIME: 500±12 HOURS 3. LOAD: ALLOWED DC CURREN
HUMIDITY LOAD LIFE TEST		1. TEMPERATURE: 60±2°C 2. R.H.: 90-95% 3. TIME: 500±12 HOURS 4. LOAD: ALLOWED DC CURREN

PRODUCT	UU10.5LF-102-CM	COIL SPECIFICATION	DATE	2005/3/2
SPEC.NO.	C-5110-014(02)		CODE NO.	C05110014


RECOMMENDED SOLDERING CONDITIONS :

CLASSIFICATION REFLOW PROFILES

Profile Feature	Sn-Pb Eutectic Assembly		Pb-Free Assembly	
	Large Body	Small Body	Large Body	Small Body
Average ramp-up rate (T_L to T_P)	3°C/second max.		3°C/second max.	
Preheat				
-Temperature Min (T_{smin})	100°C		150°C	
-Temperature Min (T_{smax})	150°C		200°C	
-Time (min to max) (ts)	60-120 seconds		60-180 seconds	
T_{smax} to T_L				
-Ramp-up Rate			3°C/second max.	
Time maintained above:				
-Temperature (T_L)	183°C		217°C	
-Time (t_L)	60-150 seconds		60-150 seconds	
Peak Temperature (T_P)	225 +0/-5°C	240 +0/-5°C	245 +0/-5°C	255 +5/-5°C
Time within 5°C of actual Peak Temperature (t_p)	10-30 seconds	10-30 seconds	10-30 seconds	20-40 seconds
Ramp-down Rate	6°C/second max.		6°C/second max.	
Time 25°C to Peak Temperature	6 minutes max.		8 minutes max.	

Note : All temperatures refer to topside of the package. Measured on the package body surface.


REFLOW SOLDERINGS




Murata PLA10AS1030R7R2B alternative

PRODUCT	UU10.5LF-102-CM	COIL SPECIFICATION	DATE	2005/3/2
SPEC.NO.	C-5110-014(02)		CODE NO.	C05110014

TABLE :



INNER BOX LABEL



OUT BOX LABEL

Murata PLA10AS1030R7R2B alternative



PRODUCT	UU10.5LF-102-CM	COIL SPECIFICATION	DATE	2005/3/2
SPEC.NO.	C-5110-014(02)		CODE NO.	C05110014

Cautions and Warnings :

1. All of the components are manufactured, designed, and promoted for applying in general electronics devices, for the specific area such as automotive, medical, military and aerospace except for general electronic devices.
BEC Distribution must be asked for written approval before incorporating the components into these areas.
2. The components that will be used in high-reliability / high level of safety applications should be pre-evaluated by the end customer.
Especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health.
The customer shall be responsible for evaluating and confirming the product is suitable for use in customer's applications.
3. Customer must be cautioned to verify that data sheets are the updated ones before placing orders. In the individual cases, any trouble or failure of electronic components happens during their long span cannot be eliminated even follow the instruction with existing technology.
4. Washing / Cleaning process may jeopardize the product and cause the defect. Washing agents may harm the long-term functionality of the product
5. The storage period should not be longer than 12 months (In the specific storage environment). The oxidization may happen on the terminals.
Hence all the products shall be used within 12 months after the shipping date. If the time is over 12 months, please check the solderability before use it.
6. Products should not be kept in unsuitable storage conditions, such as areas susceptible to high humidity, high temperatures, dust or corrosion.
7. Don't touch electrodes directly with bare hands as oil secretions may inhibit soldering. Always ensure optimum conditions for soldering.
8. Don't bend the terminals or subject them to excessive stress.
9. Please ensure that all terminals and case lugs are completely fixed with solder onto PCB
10. Ensure the tuning slug or cap is not fixed by solder flux during the production process.
11. Avoid placing coils near the edge of the PCB
12. Don't touch any exposed winding part and avoid coming into contact with the guide of the electrode in automatic mounting
13. The inductor / coil / common mode choke generates heat when current is applied. Please take care of this during the design.
14. Always handle the product with care to prevent the damage.
15. Our specification specifies the quality of the component as a single unit. Please ensure the component is thoroughly evaluated in your application circuit.
Even for customized products, conclusive validation of the component in the circuit can only be carried out by customer.
16. The general testing condition is in the room temperature 25 +/- 5°C and humidity under 65% RH, which is applied to all products.
17. If have any query, please feel free to contact our sales department.