



SMA Connector Series

RE-C-SMA011 SMA Connector Series

Electrical Specifications

Impedance: 50 Ω
 Frequency Range
 Semi-rigid cable: 0-18 GHz
 Flexible cables: 0-12.4 GHz
 Voltage Rating : 335 volts rms.
 Dielectric Withstanding Voltage : 500 volts rms.
 VSWR :
 1.15 +0.02 f (GHz) for Straight connector typical
 1.25 +0.025 f (GHz) for Right angle connector typical
 Contact Resistance: Center contact: 2.0 mΩ
 Body: 2.0 mΩ
 Insulation Resistance: 5,000 MΩ

Mechanical Specifications

Mating: 1/4"-36 UNS thread coupling
 Cable retention: 6kgf typical
 Durability: 500 Cycles Min.
 Coupling nut retention: 18kgf Min.
 Temperature Range: -55°C to +155°C

Material

Connector body: Brass per QQ-B-626 ,gold Plating or nickel
 Center contact Male: Brass,gold Plating
 Center contact Female: Beryllium copper,gold Plating
 Insulator: PTFE
 Gasket: Silicone rubber
 Crimp Ferrule: Annealed copper

ORDER INFORMATION

Product NO.: RE-C-SMA011

Pos. NO. _____
 SMA Connector Type _____

